




P+ Digital Back Overview

| | P 65+ | P 40+ | P 45+ | P 30+ | P 25+ |
|---|---|---|--|---|--|
| Description | World's first full frame medium format digital back, featuring Sensor+ with a choice of 60.5 megapixels for finest resolution or scaled full frame captures for fast workflow and low light versatility. | Fastest digital back with up to 1.8 fps in Sensor+ mode. A choice of 40 or 10 megapixels and an ISO range from 50 to 3200 makes this digital back the most versatile tool in the range. | High resolution shooter with unlimited burst sequences and optimized for large format photography with live preview functionality for easy composition and focus checking. | The top quality fast fashion shooter with ISO 1600, with superior moiré control and well suited for harsh environments. | All-round shooter with unlimited burst sequences and optimized for large format photography with live preview functionality for easy composition and focus checking. |
| Sensors |  |  |  |  |  |
| Lens Factor | 1.0 | 1.3 | 1.1 | 1.3 | 1.1 |
| CCD size effective | 53.9 x 40.4 mm | 43.9 x 32.9 | 49.1 x 36.8 | 44.2 x 33.1 | 48.9 x 36.7 |
| Active pixels | 8984 x 6732 | 7320 x 5484 | 7216 x 5412 | 6496 x 4872 | 5436 x 4080 |
| Pixel size (micron) | Full res. 6 x 6 Sensor+ 12 x 12 | Full res. 6 x 6 Sensor+ 12 x 12 | 6.8 x 6.8 | 6.8 x 6.8 | 9 x 9 |
| Resolution (megapixels) | 60.5 15.0 | 40 10 | 39 | 31.6 | 22 |
| Light sensitivity (ISO) | 50-800 200-3200 | 50-800 200-3200 | 50-800 | 100-1600 | 50-800 |
| Exposure time | 1/10.000 – 1 minute | 1/10.000 – 1 minute | 1/10.000 sec. up to one hour with XPose+ technology | | |
| Image quality | 16bit-OptiColor+, 12 f-stops Dynamic+ and Lens+ technology | | | | |
| Capture time (frames per sec.**) | 1.0 1.4 | 1.2 1.8 | 0.67 | 0.8 | 0.67 |
| Battery Lifetime (up to captures/up to stand-by time*) | 2000 / 3 | 2500 / 4 | 2500 / 4 | 3000 / 4 | 4000 / 4 |
| Image buffer | 1.3 GB High Speed RAM | 1.3 GB High Speed RAM | 640 MB high speed RAM | | |
| Display | 2.2" QVGA TFT with 230,000 pixels, high brightness and contrast both indoor and outdoor, very fine details | | | | |

Results are based on testing in Phase One's testing department. Variation may be expected due to specific camera set up. Battery used for test is new 2500mAh Li+.
 *) standby Time will vary a lot depending on temperature, usage of battery and state of the back e.g. Zero Latency will increase power consumption significantly
 **) Maximum expected performance. The actual performance will be dependent on the camera model and on the camera and digital back capture modes content is subject to change without notice

Your local Phase One partner

www.phaseone.com

P 65+ Camera System



Inset image © Drew Gardner

The world's most desirable camera system

The Phase One P 65+ Camera system is designed to be a seamless extension of your creativity. Extraordinary capture becomes natural through ease of use and direct control.

Shoot digital or film with no lens or back restrictions. Take advantage of the Phase One digital lenses or use your Mamiya 645 AF/ AFD or Hasselblad V lenses for an even broader choice.

Being the benchmark for reliability and image quality, the P 65+ digital back ensures that you amaze your clients at every capture. The P 65+ offers the worlds first full frame 645 sensor, delivering astounding 60.5 megapixel captures and giving you full advantage of your medium format lenses. Sensor+ technology marks another milestone offering ultimate flexibility with scalable pixels for higher sensitivity and faster workflow.

PHASEONE

what the world's best photography is made of

P 65+ Digital Back Specifications



Inset image © Drew Gardner

- Sensor+ technology solution
- 15 mega pixel captures for faster workflow and higher sensitivity
- 60.5 mega pixel captures for astounding level of details
- Extreme 12.5 f-stops dynamic range
- True wide angle performance
- 100% viewfinder area for best composition
- Up to 1.4 frame per second capture rate

| Imaging technology | |
|--------------------|--------------------|
| CCD | Full frame CCD |
| Lens Factor | 1.0 / Full frame |
| Resolution | 60.5 mega pixels |
| Active pixels | 8984 x 6732 pixels |
| CCD size effective | 53.9 mm x 40.4 mm |
| Pixel size | 6 x 6 micron |
| Image ratio | 4:3 |
| Dynamic range | 12.5 f-stops |

| P 65+ full resolution capture mode | |
|------------------------------------|--------------------------------------|
| Resolution | 60.5 mega pixels |
| Pixel size | 6 x 6 micron |
| RAW file compression | IIQ large: 60 MB IIQ small: 40 MB |
| ISO | 50, 100, 200, 400, 800 |

| Sensor+ capture mode | |
|----------------------|--------------------------------------|
| Resolution | 15 mega pixels |
| Pixel size | 12 x 12 micron |
| RAW file compression | IIQ large: 15 MB IIQ small: 10 MB |
| ISO | 200, 400, 800, 1600, 3200 |

| Output files | |
|--------------------|---|
| Color depth | 16 bit per color |
| Image file formats | All output formats of Capture One are possible: TIFF-RGB, TIFF-CMYK, JPEG |
| Color management | RGB, Embedded ICC profile, CMYK |

| LCD screen | |
|---------------|----------------|
| Size | 2.2" |
| Resolution | 230,400 pixels |
| Viewing angle | 160° |

| Lighting | |
|--|--|
| Supports all photographic lights: Flash, tungsten, daylight, fluorescent, HMI | |

| Operating conditions | |
|----------------------|-------------------------------|
| Temperature | 0° to 40°C (32° to 122°F) |
| Humidity | 15 to 80% RH (non-condensing) |

| Computer minimum requirements | |
|-------------------------------|---|
| Mac | Fast Intel Core™ 2 Duo or later CPU, 4 GB RAM, Fast HDD; RAID 0 configured systems for max performance, Nvidia 8800 series graphics card or newer |
| PC | Intel® Pentium® 4, 2 GB RAM, 10 GB free hard disk space, IEEE 1394 interface, Windows XP®, Service Pack 3 or Windows Vista®, Service Pack 1 |

| P+ back mounts | |
|-------------------|---|
| Phase One/ Mamiya | Phase One 645 AF/DF, Mamiya 645AFDII/ AFDIII, Mamiya RZ67 PRO IID via adaptor |
| Phase One H101 | Hasselblad H1 and H2 |
| Hasselblad V | Hasselblad 555ELD, 553ELX, 503CW and 501CM Via adaptor: Mamiya RZ67 Pro II Mamiya RB67 |
| Contax | Contax 645 |

| Wide angle & technical cameras | |
|--|--|
| 4 x 5" via FlexAdaptor: Arca Swiss, Cambo, Linhof, Toyo, Sinar, Plaubel, Horseman. | |

| Storage files | |
|--|--|
| Phase Ones IIQ RAW file format speeds up the image capture and file transfer. It increases the storage capacity by turning the full 16 bit image data into a compact RAW file format. The default IIQ RAW-large format is completely lossless. | |

| Software | |
|----------------------------|--|
| Capture One 4.6.2 or later | |

| Certifications | |
|----------------|--|
| CE | |

content is subject to change without notice

645 AF Camera Body Specifications



- Open platform for maximum choice and compatibility
- Durable, proven platform for secure operation
- Ergonomic handling and ease of use
- Use Phase One digital lenses, Mamiya AF/AFD lenses or Hasselblad V lenses
- Guaranteed up to 300.000 captures or 3 years (VA)
- Exposures from 1/4000s to 60 minutes
- Prepared for use with leaf shutter lenses

Shutter speed from 1/4000s to 60 minutes, B and X modes can match the extreme long exposure capability of the P+ digital backs or stop action with fast shutter speed or flash.

The mirror and viewfinder of the Phase One 645 camera are almost three times larger than those of 35mm cameras, providing much greater control of focus and composition.

While hosting a complete list of features and custom functions, the Phase One 645 camera is extremely easy to use. All settings important to the exposure are easily controlled by manual dials and soft buttons.

| | |
|----------------|--|
| Camera type | Modular 645 AF SLR body |
| Lenses | Phase One Digital and Mamiya 645 AFD Compatible with Hasselblad V lenses Ready for leaf shutter lenses |
| Backs | Digital back and film ready Open platform back mount |
| Auto focus | TTL phase-difference AF with 3 focus points Focus confirmation in manual mode Infrared AF assists for unfailing focus Auto focus lock for swift AF/ M shift |
| Shutter | 1/4000s to 60 minutes Up to 2 fps Shutter speed bracketing |
| Flash | Focal plane shutter: Up to 1/125s Leaf shutter lenses: Up to 1/800s' 1 st and 2 nd curtain flash synchronization X sync terminal and support for TTL flash |
| Light Metering | TTL metering (average, spot and auto) Programmable AEL button Exposure compensation: +/- 5EV |
| Mirror-Up | Electronically-activated by switch on grip |

| | |
|--------------------|--|
| Viewfinder | Fixed prism viewfinder Exchangeable diopter from -5 to +3 LCD panel with full exposure information |
| Focusing Screen | Interchangeable focus screens Laser engraved mask for digital back Matte, Grid, Checker, Microprism |
| Selftimer | Self-timer from 2 to 60 sec |
| Remote | Screw-in cable release on shutter button Terminal for electronic triggering devices |
| Stop Down Preview | Stop down button on front of camera |
| Tripod Socket | 1/4 inch and 3/8 inch included |
| Power Requirements | 6 AA batteries (standard or rechargeable) External battery pack – 6 AA batteries External AC adapter |
| User configuration | 3 user presets for capture settings 36 custom settings Customizable dials and buttons |
| Size | W, H, D // 6, 5, 7.2" // 153, 128, 184mm |
| Weight | 61oz. / 1730g. w/o batteries |

content is subject to change without notice